Trade Waste Monitor Systems

Continuous monitoring of waste streams to Trade Waste Authority requirements

Allied Pumps Trade Waste Monitor Systems provide continuous monitoring of waste streams to meet Trade Waste Authority requirements. Systems are supplied as integrated components or as complete packages, in compact above ground or remote below ground configurations. An automated closure valve isolates the line and a remote alarm signals any out of parameter condition.

KEY FEATURES

- Automated Closure Valve for Line Isolation in Alarm Conditions
- Remote Alarm, Audible and Visual With Mute Switch
- Chart Recorder for Continuous Recording of All Monitored Conditions
- Stainless Steel Enclosure
- Compact or Remote Configuration
- Below Ground Pit Package With Internal Pipework and Components
- Delivered to Site Ready for Installation

PRODUCT APPLICATIONS

- Commercial Kitchens
- Laundromats
- Aquatic and Leisure Centres
- Sewer Lines
- Sites Subject to Trade Waste Discharge Limits



PRODUCT SPECIFICATION

Model No.	Nominal Size (L/h)	Gravity Flow (L/s)		Type	Pit Ø (mm)	Pit Depth (mm)
		Min.	Max.			
APTW-M40-C	40	0.12	1.00	Compact	-	-
APTW-M50-C	50	0.19	1.60	Compact	-	-
APTW-M65-C	65	0.30	2.70	Compact	-	-
APTW-M80-C	80	0.50	3.30	Compact	-	-
APTW-M100-C	100	0.70	6.20	Compact	-	-
APTW-M150-C	150	1.70	14.00	Compact	-	-
APTW-FS1000/4000-M40R	40	0.12	1.00	Remote	1,200	1000 to 4000
APTW-FS1000/4000-M50R	50	0.19	1.60	Remote	1,200	1000 to 4000
APTW-FM1000/6000-M65R	65	0.30	2.70	Remote	1,800	1000 to 6000
APTW-FM1000/6000-M80R	80	0.50	3.30	Remote	1,800	1000 to 6000
APTW-FM1000/6000-M100R	100	0.70	6.20	Remote	1,800	1000 to 6000
APTW-FM1000/6000-M150R	150	1.70	14.00	Remote	1,800	1000 to 6000